



Phone (317) 841-7727 ~ Fax (317) 842-7761
Toll Free (800) 307-7727

ORDER QUOTE ONLY

BILL TO: _____

ATTN: _____

SHIP TO: _____

ATTN: _____

Same

HOMEOWNER: _____

ATTN: _____

SHIPPING INFORMATION

- Ship-out as single shipment Pre-ship required
Orders with pre-ships will incur additional freight and crate charges.
- Pick-up
- Installation – with builder providing boxset
- Installation – with Coverstar Central providing boxset
- On-Site Training

Pre-ship P.O. #: _____

System Order P.O. #: _____

Need By Date: _____

COVER DIMENSIONS - Inside of track to inside of track

Track Width Track Length Setback Sq. Ft.
 X + =
Feet Inches Feet Feet

The appropriate amount of fabric will automatically be added to account for slack and roll-up to insure that the cover can be correctly installed and that the system will operate properly.

SYSTEM TYPE

- Full System
- Cover Only
- Torque
- Auto Spa
- Manual

POWER OPTIONS

- Electric Standard
 - Electric High
 - Hydraulic
- How much hose do you

Feet (one-way)

SYSTEM APPLICATION

Unit Type

- Deck Mount Recessed Underguide Cover Only
- Bench Frame Only
- Build Wood Bench Type _____
- Build PVC Plastic Bench Color _____

Motor Side – Standing behind the system & looking out over the pool.

- Left Side Right Side

NOTES: _____

Track Type

- Deck Mount
- Standard TG 403

Recessed

- Standard TG 403
- Flush Horizontal - Gray
- Flush Horizontal - Tan
- Flush Vertical - Gray
- Flush Vertical - Tan

Underguide

- Standard UG 403
- Encapsulated Gunitite
- Encapsulated Gunitite w/ Fiber
- Encapsulated w/ Liner
- Encapsulated w/ Liner w/ Fiber
- Encapsulated Pool-N-Pool
- Other _____

Corners – You must choose one when using Encapsulation w/ Liner

- 90 deg 3" chop 6" radius 2' radius

Coping Style

- Clip-on Bull Nosed Rounded Inclined

- Reusable 1 piece - Cantilever 2 piece - Bull Nose
- 1 piece - Incline 2 piece - Cantilever
- 2 piece - Incline

FABRIC COLOR

- UG II Navy Blue Royal Blue Light Blue
 - Aqua Forest Green Tan
 - Gray Charcoal Gray OTHER
- Please specify special order color in "Notes" section below*

WEBBING

- Color Match Weld-on White Weld-on Sewn
- Color Match Webbing NOT available in Aqua Color*

LID APPLICATION

- Standard Lid - You must choose a hinge size below
 - 4" Standard (For standard 12 5/8" box size)
 - 6" Upgrade (For 14" boxes or polymer housing w/ UG track)
 - 9" Upgrade (For 14+ " boxes or polymer housing w/ TG track)
- 12 5/8" Flush Lid (Includes four (4) walk-on brackets – C22A0504)
- 14" Flush Lid (Includes four (4) walk-on brackets – C22A1421)
NOTE: Additional brackets required with the flush lid to make it fully walk-on Requires one bracket every two (2) feet. If you need additional brackets, check item below.
- 12 5/8" Box Form Encapsulation (Consumable for Lid Forming System)
- 14" Box Form Encapsulation (Consumable for Lid Forming System)
- 12 5/8" Lid Forming System (Shape Kit sold separately)
- 14" Lid Forming System (Shape Kit sold separately)

- Pan Lids (Standard Lid turned upside down – 2' sections)
- No Lid Required

BRACKETS

- Standard 90 deg (Use w/ Underguide system application)
- Standard 105 deg (Use w/ Recessed Topguide system application)
- Adjustable Walk-on for 12 5/8" aluminum lids
- Adjustable Walk-on for 14" aluminum lids
- Adjustable Walk-on for stone lids
- Custom Bracket _____

Describe – Price will depend on size and material costs

- No Brackets Required

- Flat Extension for adjustable walk-on brackets
- "T" Extension for adjustable walk-on brackets

OTHER OPTIONS

- Polymer Housing (appropriate mounting kit will also be added)
- Extra Key Switch
- Ladder Hinges QTY _____

NOTES: _____

